



Pull-off Testers

DY-216

Automated pull-off tester with a mid-range instrument suitable for most pull-off testing applications



Accuracy

The ideal calibration accuracy EN ISO 7500-1 Class 1, suitable for most pull-off testing applications, with live view of actual load rate graph



Performance

Leverage the comprehensive range of test discs plus adjustable foot configuration to cover a wide variety of mid-range applications



Ease of use

Easy to operate even on overhead walls, combined with a simple programming process of key parameters and a fully automated test



Processing Unit / Sensor

Working Range	0.81 to 8.1 MPa (118 to 1182 psi)
Tensile force (50 mm test disc)	1.6 to 16 kN (60 to 3597 lbf)
Maximum Stroke	5 mm
Maximum Pulling Speed	4.65 mm/min (0.183 inch/min)
Instrument Firmware	Maximum load Actual load rate Test duration Complete report of the test Failure mode reporting Full data review on instrument
PC Software	DY-2 Link with a live view of actual load rate graph
Memory	100 measurements
Connections	USB to PC and for charging
Calibration Accuracy	EN ISO 7500-1 Class 1 (± 1 % from 20 % of maximum force)
Battery Capacity	1500 mAh, 3.7V (min. 80 measurements)
Weight	4.5 kg
Applications:	✓ Adhesive strength of mortars and renders ✓ Adhesive strength of asphalt ✓ Adhesive strength of tiles ✓ Bond strength of coatings and overlays ✓ Bond strength of repair materials such as FRP ✓ Tensile strength in concrete renovation

SWISS  MADE

Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.

www.screeningeagle.com

[Request a quote](#)