

WS 1720 RR ESD



Design

Material	
Seat / Backrest	leatherette / leatherette
Five star base xx20 Ø655mm with dual castors (Ø 65mm)	diecast aluminium unloaded braked - loaded unbraked
Column xx20	safety gas spring, chrome plated, with column cover
Backrest steel bar	high-precision steel bar, Ø100 x 26mm
Total height *	960 to 1220mm
Thickness of seat / backrest *	95mm / 115mm
Weight *	18.20kg
Loading capacity	kg

Adjustabilities

Seat height (acc. DIN 68877) *	510 to 630mm
Seat tilt *	-4° to +10°
Seat lock	continuous
Backrest tilt *	-6° to +8°

Details

Backrest	
Width top / bottom *	340 / 455mm
Height *	520mm
Seat	
Width front / back *	510 / 480mm
Depth *	470mm

Characteristics

Conductivity	10 ⁴ Ohm to 10 ⁶ Ohm acc. EN 61340-5-1-1
Certified for class-5 clean rooms according to the DIN EN ISO 14644-1 standard.	
Werksitz leatherette is urine-, blood-and sweat-resistant in accordance with the DIN 53160 standard.	
*: production- or model-related differences are possible	
Revision status	09.12.2015

We are constantly developing our products for you in design as well as in quality. Please contact us about your special requirements for work places and employees. We offer you individual solutions for special seat and standing work places.

WS 1720 RR ESD

 **Fraunhofer**
IBMT



*: The illustrated product may show accessories with surcharge.