

## Precision incubator

### Model IF260



## Standard equipment

### Ventilation and Control

- forced air circulation by quiet air turbine, adjustable in 10 % steps
- adjustment of pre-heated fresh air admixture by air flap control in 10 % steps
- vent connection with restrictor flap
- adaptive multifunctional digital PID-microprocessor controller with high-definition TFT-colour display
- self-diagnostics for fault analysis
- 1 Pt100 sensor DIN class A in 4-wire-circuit
- Digital backwards counter with target time setting, adjustable from 1 minute to 99 days
- parameters adjustable on ControlCOCKPIT: temperature (Celsius or Fahrenheit), fan speed, air flap position, programme time, time zones, summertime/wintertime
- SetpointWAIT function - the process time does not start until the set temperature is reached
- AtmoCONTROL software for reading out, managing and organising the data logger via Ethernet interface (temporary trial version can be downloaded). USB stick with AtmoCONTROL software available as accessory (on demand).

- Setting of languages on ControlCOCKPIT: German/English/Spanish/French
- resolution of display for setpoint and actual temperature values 0.1 °C
- calibration facility directly at ControlCOCKPIT for three freely selectable temperature values
- programme stored in case of power failure
- incl. works calibration certificate for +37 °C

### Overtemperature protection (double)

- adjustable electronic overtemperature monitor and mechanical temperature limiter TB, protection class 1 according to DIN 12880 to switch off the heating approx. 20 °C above nominal temperature

### Textured Stainless Steel Casing

- w x h x d: 824 x 1183 x 684 mm
- fully insulated stainless steel door with 2-point locking (compression door lock)
- inner glass door
- rear zinc-plated steel

### Interior - Heating Concept

- w x h x d: 640 x 800 x 500 mm, 256 l, Depth (less 39 mm for fan)

- easy-to-clean interior,made of stainless steel,reinforced by deep drawn ribbing with integrated and protected large-area heating on four sides
- 2 stainless steel grids
- Max. loading of chamber: 300 kg

**Temperature Range**

- min. 10°C above ambient up to +80°C

**Voltage / Power Rating**

- 230 V (+/- 10 %), 50/60 Hz / approx. 1.700 W
- 115 V (+/- 10 %), 50/60 Hz / approx. 1.100 W

**Packing Data**

- net weight approx. 110 kg

- gross weight carton approx. 161 kg
- dimensions approx.:  
carton w x h x d: 93 x 138 x 93 cm
- the appliances must be transported upright

**Customs Tariff Number**

- 8419 8998

**Country of Origin**

- Federal Republic of Germany

**WEEE-Reg.-No.**

- DE 66812464