

Data Sheet

Mixing / Magnetic Stirrers



Midi MR 1 digital

Powerful magnetic stirrer without heating function.

- Stirring quantity up to 50 liters (H2O)
- Flat, sturdy stainless steel casing
- Non-locking motor
- Infinitely variable speed
- Digital LED speed display
- Timer (0 - 56 min) or continuous operation
- Integrated USB and RS 232 interface

Accessories: IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 40 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 50 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 80 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 40 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 50 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 50 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 40 Set (5 Pcs)

Technical Data	
Number of stirring positions	1
Stirring quantity max. per stirring position (H2O) [l]	50
Motor rating output [W]	19
Speed range [rpm]	0 - 1000
Stirring bar length max. [mm]	80
Self-heating of the hotplate by max. stirring (RT:22°C/duration:1h) [+K]	28
Set-up plate material	stainless steel 1.4301
Set-up plate dimensions [mm]	350 x 350
Dimensions (W x H x D) [mm]	360 x 110 x 430
Weight [kg]	10.7
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 21
RS 232 interface	yes
USB interface	yes
Voltage [V]	230 / 100 - 120 / 100
Frequency [Hz]	50/60
Power input [W]	70
Ident. No.	0025002968

slide round PTFE-coated Magnetic stirring bars, IKAFLON® 50 Set (5 Pcs)
slide round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs)
ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs)
ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 35 Set (5 Pcs)
ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 40 Set (5 Pcs)
ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 50 Set (5 Pcs)
ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 60 Set (5 Pcs)
ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 70 Set (5 Pcs)
ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs)
cross PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs)
cross PTFE-coated Magnetic stirring bars, IKAFLON® 38 Set (5 Pcs)
cross PTFE-coated Magnetic stirring bars, IKAFLON® 37 Set (5 Pcs)
bone PTFE-coated Magnetic stirring bars, IKAFLON® 54 Set (5 Pcs)
bone PTFE-coated Magnetic stirring bars, IKAFLON® 74 (1 Pc)
beaker PTFE-coated Magnetic stirring bars, IKAFLON® 103 (1 Pc)
beaker PTFE-coated Magnetic stirring bars, IKAFLON® 125 (1 Pc)
beaker PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs)
PTFE-coated Magnetic stirring bars, TRIKA® 35 Set (5 Pcs)
PTFE-coated Magnetic stirring bars, TRIKA® 55 Set (5 Pcs)
PTFE-coated Magnetic stirring bars, TRIKA® 80 Set (5 Pcs)
PTFE-coated Magnetic stirring bars, H 11 Mains cable Euro plug, H 11 Mains cable CH plug, RSE Stirring bar remover, H 11 Mains cable UK plug, H 11 Mains cable USA plug